

P

Effective Date: 03-01-93

Supersedes: _____

PRELIMINARY

Specification for Philip Morris Converted Tipping Paper

BRAND(s): CABARRUS ONLY — Merit Ultra Lts Res FTO - GCC / IRANBRAND CODE(s): 01800 (GCC) / (IRN) + 01010 (GCC) / 1 (IRN)BOBBIN DIMENSIONS: 64mm x 3500 MBASE SHEET: KC 236 M2BOBBIN DESCRIPTION: CORK / WH + 5GLLSUNPERFORATED MATERIAL CODE: 11-298-A

CONVERTER: _____

PERFORATED MATERIAL CODE: 12-379-A

QUANTITY: _____

LOCATION: Cabarrus: X Louisville: _____ Richmond: _____PERFORATION R.T.D.: .6 CM ± .1 CMNUMBER OF ROWS: 2HOLES / INCH / ROW: 35 TO 45

A. Distance between Perforation Bands

24.00 mm ± 1.00 mm

B. Perforation Band Width

1.50 mm ± .50 mm

C. Distance Between Perforation Rows w/in Each Band

_____ ± _____

D. Edge of Perforation Band to Edge of Tipping Paper

15.50 mm ± 1.00 mm

REPLACEMENT INSTRUCTIONS:

per North
Distrib 3/1/93
@ 1450.

Effective Immediately: (Do not use up Present Tipping Inventory Now) (Richmond S/S will ^{continue with} ~~replace~~ 12-119-A)

Use Up Present Material until Inventory is Exhausted: OK to mix in pack / carton / case

Use Up Present Material until Inventory is Exhausted: Do Not mix in pack / carton; OK to mix in case

Use up Present Material until Inventory is Exhausted: Do Not mix in pack / carton / case

DILUTION TARGET _____

COMMENTS: PERFORATION CHANGED FROM .40 CM ± .10 CM
(12-119-A) TO .6 CM (12-379-A) TO BRING
TAR LEVELS TO TARGET FOR CABARRUS ONLY.

PREPARED BY: KarenAPPROVED BY: Eli Wanta

Distributed to:

S. Cline
A. DavisD. Fessel / B. Clark
S. Heywood / J. EllisS. Rogers / R. Wray
A. Thorpe

2054446447